

LIGHTING

LED FLOODLIGHTS



VELOCITY SERIES

Designed for performance, reliability and ease of installation, the Velocity Floodlight is the perfect option for commercial applications. Its high efficacy of 130 lumens per watt delivers optimum performance, complemented by a diffused lens and adjustable bracket which enables easy installation across a range of applications.

With an IP65 rating and tolerance across a wide ambient temperature range, the Velocity Series is built to last.

FEATURES

- User friendly driver compartment and large 6mm terminal block
- 2x25mm and 2x20mm conduit entries
- Ease of installation (no bracket removal required and hinge lid to terminal block)
- Supply is cut-off to driver when lid is opened
- High efficacy
- IP65 rating

SPECIFICATIONS

POWER FACTOR	>0.9	MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LUMENS	EFFICACY
CRI	>80	EP-VEL-70	5000K	340x100x495mm	70	69.81	9279	133lm/W
BEAM ANGLE	110°	EP-VEL-100	5000K	340x100x495mm	100	99.32	13070	132lm/W
IP RATING	65	EP-VEL-120	5000K	340x100x495mm	120	120	15580	130lm/W
LIFETIME (L70)	>70,000h	EP-VEL-150	5000K	340x100x495mm	150	149	18497	124lm/W
WARRANTY	5 Years	EP-VEL-200	5000K	380x100x555mm	200	200.1	26821	134lm/W

